

## J2 ROOF COAT MSDS

J2 Chemistries 2990 East Washington, Suite 113, Phoenix, AZ 85034 Phone: 888-952-1010

### I. PRODUCT IDENTIFICATION

**PRODUCT NAME:** J2 ROOF COAT  
**CHEMICAL FAMILY:** ACRYLIC POLYMER, POLYMER BLEND  
**CHEMICAL NAME:** N/A  
**SYNONYMS:** ELASTOMER COATING

---

### II. HAZARDOUS INGREDIENTS

<u>INGREDIENTS:</u>	<u>CAS #</u>	<u>CONCENTRATION (% BY WEIGHT)</u>
ACRYLIC POLYMER BLEND	NOT HAZARDOUS	35 MAX
TITANIUM DIOXIDE	13463-67-7	35 MAX
ZINC OXIDE	1314-13-2	6 MAX
CALCIUM CARBONATE	1317-65-3	40 MAX
HYDRATED ALUMINA	21645-51-2	30 MAX
WATER	7732-18-5	40 MAX

\*\*NO TOXIC CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III AND OF 40 CFR 372 ARE PRESENT IN THIS PRODUCT.

---

### III. PHYSICAL DATA

PHYSICAL FORM:	MILKY WHITE LIQUID
BOILING POINT:	212°F
VAPOR DENSITY (AIR=1)	< 1
VAPOR PRESSURE:	> 1
EVAPORATION RATE:	< 1
SOLUBILITY IN WATER:	SOLUBLE
VOC %:	< 23 GAL

---

### IV. FIRE & EXPLOSION DATA

FLASH POINT:	NON-FLAMMABLE, NON-COMBUSTIBLE
FRAMABILITY CLASSIFICATION::	N/A
AUTO-IGNITION TEMPERATURE:	N/A
EXTINGUISHING MEDIA: .	n/a

**SPECIAL FIRE FIGHTING PROCEDURES:** For fires involving this material, do not enter any enclosed or confined space **without** proper protective gear, including self-contained breathing apparatus to protect against the hazardous effect of the normal products of combustion or oxygen deficiency.

---

### V. HEALTH EFFECTS DATA

<b>HUMAN EFFECTS OF OVEREXPOSURE:</b>	
<b>INHALATION:</b>	Vapor or mist may cause irritation of the nose, throat and lungs..
<b>EYES EXPOSURE:</b>	Possible slight irritation to eyes with direct contact.
<b>SKIN EXPOSURE:</b>	Possible skin irritant with repeated or prolonged contact.

## VI. EMERGENCY & FIRST AID PROCEDURES

EYE CONTACT & SKIN CONTACT: Flush eyes with large amounts of water for at least 15 minutes. Wash affected skin areas with soap and water. See a physician if irritation persists.

INHALATION: Move subject to fresh air.

INGESTION: If swallowed give two glasses of water to drink. See a physician.

---

## VII. REACTIVITY DATA

STABILITY: STABLE

POLYMERIZATION: WILL NOT OCCUR.

INCOMPATIBILITY: NONE

HAZARDOUS DECOMPOSITION PRODUCTS: ACRYLIC MONOMERS.

CONDITIONS TO AVOID: KEEP FROM FREEZING

---

## VIII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN WHEN MATERIAL IS SPILLED OR RELEASED: Keep spectators away. Floor may be slippery; use care to avoid falling. Scoop or shovel solid material into a suitable container for recovery or disposal. Keep spills out of municipal sewers and open bodies of water.

WASTE DISPOSAL METHODS: WASTE MATERIAL MAY BE INCINERATED OR DISPOSED OF PER LOCAL, STATE AND FEDERAL REGULATIONS.

EMPTY CONTAINER PRECAUTIONS: DISPOSED OF CONTAINERS ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS.

---

## IX. SPECIAL PRECAUTIONS& STORAGE DATA

STORAGE TEMPERATURE: KEEP FROM FREEZING, STORE OUT OF DIRECT SUNLIGHT ON PALLETS, STORE INSIDE STORAGE AREA.

---

## X. REGULATORY INFORMATION

U.S. Toxic Substances Control Act (TSCA) All components of this product are believed to be in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical substances Inventory.

We believe that the information contained in this MSDS is current. Since the use of this information and the conditions of use of the product are not within our control, it is the users obligation to determine the conditions for safe use of this product. The information herein is given in good faith, but no warranty, expressed or implied, is made.