



SEALERS AND COATINGS

SUREFINISH

SACRIFICIAL FLOOR PROTECTION



View More Info for this Product at
www.surecretedesign.com/product/industrial-floor-wax

SUREFINISH

SACRIFICIAL FLOOR PROTECTION

DESCRIPTION

SureFinish™ is an industrial floor finish providing exceptional performance and adherence to both resilient and non-resilient hard surface interior flooring. It may be applied like a conventional floor finish to terrazzo, quarry tile, brick, slate, unglazed ceramic tile, Mexican tile, and stone surfaces. Additionally, **SureFinish** is recommended for use on vinyl asbestos, vinyl, reinforced vinyl, asphalt, and other types of resilient floors. It's superior scuff, scratch, and detergent resistance insures maximum wear with a minimum of maintenance. It is available in both a gloss and matte finish.

SureFinish is specifically designed to provide superior protection for interior SureCrete overlays and **Eco-Stains** that have been sealed with any of SureCrete's sealers. It acts as a sacrificial wear coat that will indefinitely protect the sealer beneath it. **SureFinish** will enhance the luster without obscuring the beauty of the surface.

APPLICATION

SureCrete Surfaces

After sealer has cured, **SureFinish** may be applied by mop. Protect the mop bucket with a trashcan liner to prevent contamination of **SureFinish**. The mop should be a closed loop finish mop head to prevent leaving "strings" in the finish product. Fully saturate the mop head and wring out so that mop is damp, but not dripping. Apply thin - medium coats until desired initial gloss is achieved (usually 2-3 coats minimum). For optimum results burish between coats using a white or non-aggressive floor pad. Between coats allow the floor to dry to the touch and wait 15 additional minutes.

General Surfaces

Completely strip off old floor finish with heavy duty floor stripper. Remove all traces of stripper and old floor finish residue. Rinse with cool clean water until clear (min. 2 - 3 times). Allow floor to dry completely. Proceed as previous described with mop, etc.

Stone

Test a small area for adhesion, prior to full application, as stone surfaces are extremely variable in nature.

Marble

Remove any polished surface with sand screen prior to application.

Maintenance

Dust mop daily using an untreated mop head to remove loose dirt, dust, and soil. Wet mop to clean ground in soil as needed. Machine scrub heavily soiled areas and reapply thin coats of **SureFinish** as needed. Heavily trafficked areas may require monthly reapplication.



PACKAGING

1 gal (3.8 L) pail
5 gal (18.9 L) pails

AVAILABLE OPTIONS

Available in both *Matte* and *Gloss* finishes

COVERAGE

First Coat: Approx 1,500 ft² (139 m²) per gallon (3.8 L)
Subsequent Coats: Approx 2,000 - 3,000 ft² (186 - 279 m²) per gallon (3.8 L)

SLIP RESISTANCE

Meets **ASTM 2047** standard for slip resistance in floor coatings. The addition of **SureFinish** to any surface will increase slip resistance.

SHELF LIFE

Under normal conditions: when kept dry and moisture free, out of direct sunlight, the shelf life of an unopened container is (12) months from the date of purchase. Storage must be under roof and off the floor. Avoid temperature extremes. Rotate inventory to maintain product that is within limits.

SUITABILITY SAMPLE

Due to condition specific sites, always prepare an adequate number of test areas. Wear protection system and aesthetic suitability for products' intended use should be included. On site sample approval is especially critical on substantial, heavy traffic situation.

CLEAN-UP

Once SureGrip is mixed into sealer or broadcast onto selected surface, it is nearly impossible to remove while still keeping the sealer viable. If spilled onto dry surfaces, SureGrip can be easily swept up and re-used.

DISPOSAL

Contact your local government household hazardous waste coordinator for information on disposal of unused product.

LIMITATIONS

- For use by trained professionals that have read the complete SDS.
- Product performs best upon a concrete slab that has no ponding of standing water.
- When masking use caution while taping to a floor that is not completely cured, especially at edges, as delamination may occur.
- Protect from metal wheel traffic and some furniture where point of contact may be damaging.
- Chemicals used in tire manufacturing may be detrimental to all sealers from vehicular parking.

WARRANTY

Warranty of this product, when used according to the directions, is limited to refund of purchase price, or replacement of product (if defective), at manufactures/seller's option. SureCrete Design Products shall not be liable for cost of labor or direct and/or incidental consequential damages.

CAUTIONS

KEEP OUT OF REACH OF CHILDREN. Product is flammable. Avoid sources of ignition. Keep areas ventilated to prevent the accumulation of vapors. **Inhalation:** Use NIOSH approved respirator for organic vapors. **Skin Contact:** Skin contact may cause irritation. Remove contaminated clothing and wash affected skin with soap and water. Launder clothing before reuse. If symptoms persist, seek medical attention. **Eyes:** Wear safety eye protection when applying. If contact occurs, flush eyes with water for 15 minutes, seek medical attention.

SAFETY DATA SHEETS

The following are links to all available safety data sheets related to this product:

- [surefinish-sds.pdf](#)

PRODUCT PART #'S

Gloss 1 Gallon Jug	SKU# 55102014
Gloss 5 Gallon Pail	SKU# 55102015
Matte 1 Gallon Jug	SKU# 55102016
Matte 5 Gallon Pail	SKU# 55102017