



Convergent Concrete Technologies, LLC.

Specialty Chemical Concrete Treatments Commercial

Products Group 115 North 1380 West Orem, Utah 84057 United States of America Office: 801-375-2280 Fax: 801-375-2971

www.convergent concrete.com

PRODUCT DESCRIPTION

Pentra-Finish™ (HG) is a patented, high-gloss, stain and wear resistant finish for improving the sheen, hardness and chemical resistance of natural and cast stone, terrazzo, masonry, and other cement-based surfaces. This water-based, lithium fortified chemical polish dries quickly to a clear, extremely hard, micro-coating that tenaciously bonds and reacts with the substrate forming an insoluble bond. Formulated using reactive silicon hybrid polymer technology (SiRE)™ for extreme gloss, rapid shine development and excellent wear properties, this novel treatment eliminates the need for floor waxes, liquid polishes and conventional resin based coatings. Best results and coverage will be obtained by densifying the surface with approved Nano-Lithium® Densifier before applying Pentra-Finish™ (HG).

Because of its unique chemistry, **Pentra-Finish™ (HG)** will not lift or peel from the surface. Periodic recoating requires no stripping as the material doesn't build up. **Pentra-Finish™ (HG)** is non-toxic, non-hazardous, and VOC compliant in all areas of the world with less than 50 grams per liter VOC content. The easy-to-use finish is tough, mark-resistant, fast drying and non-streaking. The treatment is used in conjunction with a high-speed burnisher on non-porous stone, masonry and Portland cement based building materials to provide superior clarity and improved resistance against water and water-borne stains from accidental spills, oils, dirt and grime. Ideal for ground and polished concrete surfaces as well as integrally colored, dyed and/or stained concrete. **Pentra-Finish™ (HG)** enhances the color intensity of natural and cast stone, and integrally colored, dyed, or acid stained decorative concrete.

KEY BENEFITS

- Delivers rapid shine development with increased abrasion and stain resistance as well as superior gloss retention
- Keeps dirt and contaminants from penetrating, making cleaning faster, more effective and more economical
- Ready to use in a few hours--rapidly cures into a durable finish for facilities that require maximum protection and little-to-no downtime
- Forms a protective "micro surface layer" that is breathable, dense, abrasion resistant, and that will not peel or flake
- Reduces maintenance, cleaning costs and costly repairs-simply damp mop or machine scrub
- No build up--periodic re-application is simple and requires no stripping
 Prolongs shine of polished concrete surfaces
- Safe for food contact per SGS Testing (21 CFR 175.300)

CUSTOMER SERVICE:

(1-866-375-2280) to verify the most current versions, visit our website: www.convergentconcrete.com or scan the code.



USES

INTERIOR FLOORING NON-POROUS GROUND, HONED, POLISHED OR BURNISHED CONCRETE SURFACES

Commercial: Grocery Stores, Office Building, Retail, Banks, Malls, Warehouses, Distribution Centers

Industrial: Food Processing Facilities, Cold Storage / Freezers, Beverage and Manufacturing Plants

Institutional: Churches, Hospitals, Universities, Schools, Museums Theme & Leisure: Resorts, Hotels, Casinos, Restaurants, Theaters

Governmental: Federal & State Buildings, Prisons

Residential: Concrete floors and Garages

APPLICATION

BEFORE APPLICATION, ALWAYS DO A SMALL TEST SAMPLE IN A LESS-VISIBLE AREA TO BE SURE THERE ARE NO VARIABLES OR CONTAMINANTS IN THE SUBSTRATE THAT MAY BE INCOMPATIBLE WITH THIS PRODUCT.

Surface Preparation: Be sure surface to be treated is clean and dry. Pentra-**Finish™ (HG)** will not hide stains. Aggressive scrubbing with a neutral to alkaline cleaner is recommended. Avoid citrus or butyl compounds when cleaning. **Finish™ (HG)** will not bond to acidic surfaces so if applying over an acid stain, neutralize thoroughly first.

Mixing: Lightly stir before each use. Do not over mix or bubbles and/or foaming can occur and make uniform application more difficult.

Placement: IMPORTANT Do not over apply. Very thin coats are best. Apply Finish™ (HG) using a micro fiber pad that has been pre-dampened with water. Using a pump up sprayer or HVLP sprayer, spray lightly over the top of the area to be treated, and then spread material thinly and evenly using the micro fiber pad over the rest of the area. For best results, limit the size of the area being treated at any one time to a 20ft. x 20ft. (6.1m x 6.1m) section. Spread at a rate of 1,500-3000 sq. ft./gal. (37-74 sq. m/L) depending on porosity of the surface. Spray another line of material when the applicator pad begins to drag. Do not work material into the surface—spread it and leave it. Allow each application to dry at least 30-60 minutes between coats or before using.

Second applications will improve sheen and stain protection. Buffing with a high-speed burnisher (1500-2100 rpm) and a hog's hair pad between coats is recommended and will speed curing and improve sheen. Second coats will usually take no more than 3000-4000 sq. ft./gal. (74 – 98 sq. m/L) followed by a burnish. Do not cover treated surfaces for at least 1 week as protective coverings may slow curing and cause some whiting by trapping moisture.

ESTIMATED COVERAGE

1st coat: 1,500-3000 sq. ft./gal. (37 -74 sq. m/L)

2nd and subsequent coats: 3000-4000 sq. ft./gal. (74 – 98 sq. m/L)

Texture and absorption of surface will determine final coverage rates. Porous concrete surfaces may require additional material.

CLEAN UP

Wash equipment with soap and water. Although Pentra-Finish™ (HG) is non-toxic and environmentally friendly, it is alkaline. Use the material completely, or dry it out and dispose of it properly per local regulations. Do not pour down sanitary sewers or into storm drains.

MAINTENANCE

Routine sweeping, mopping, washing and mechanical scrubbing of floors with water and neutral pH cleaners (if necessary) is recommended. Plain water only is sufficient for most environments. DO NOT USE cleaners that are acidic or that have citrus (d-Limonene) or Butyl compounds. Although **Pentra-Finish™ (HG)** is chemically resistant and helps reduce staining, some compounds, especially acids, may damage the surface, and therefore it may not be suitable for some applications. If unsure, check with a Convergent technical representative. Regular maintenance and cleaning will help prolong surface shine. Wipe up any chemical spills as soon as possible.

SAFETY/HEALTH INFORMATION

KEEP OUT OF REACH OF CHILDREN. Dispose of waste material in accordance with federal, state and local requirements. Although the material is non-toxic and non-hazardous, the treatment is alkaline and may cause eye and skin irritation. Wear eye protection and gloves. If splashed in eyes, rinse with water and consult a doctor if irritation persists. Wash promptly from skin. Do not take internally—if swallowed, do not induce vomiting—drink water and call a physician. Avoid contact with eyes. Protective clothing is recommended. Surfaces may be slippery when wet with product. Additional precautions, safety information and first aid treatments are contained in the Material Safety Data Sheet (MSDS).

PROPERTIES

Active Ingredients: 100% of total solids

Specific Gravity: 1.09
pH: 11.5
V.O.C Content: <50g/L
Flash Point: N/A
Freeze Point: 32°F (0°C)

Shelf Life: 1 Year in unopened factory sealed container

V.O.C.

Less than 50 g/L. Compliant with all US VOC regulations including Federal EPA, OTC, LADCO, SCAOMD & CARB.

PACKAGING

1 Gal Plastic Jug 5 Gal Plastic Pail 55 Gal Drum 275 Gal tote (IBC)

LIMITATIONS

FOR PROFESSIONAL USE ONLY

Use on interior surfaces only. Protect from freezing. Agitate before use. Do not allow standing water to dwell on surface for 7 days following application. Do not allow traffic on surface until it is dry—typically 30-60 minutes. **Pentra-Finish™ (HG)** will not bridge or fill cracks, and will not salvage honeycombed or structurally unsound surfaces. **Pentra-Finish™ (HG)** quickly bonds to most surfaces including metal, wood, glass, and paint. Protect adjacent surfaces. Remove overspray quickly with a damp cloth and soap. Always do a test patch before beginning the job to verify coverage, appearance, and surface material variations.

TECHNICAL SERVICE

Customer Care Toll Free 866-375-2280 or 801-375-2280

EMAIL

technicalservice@convergent concrete.com

WEB

www.convergentconcrete.com

For chemical/medical emergencies only,

Call Infotrac 800-535-5053 Outside USA 352-323-3500

WARRANTY

The product and application information contained herein is offered in good faith and we believe it to be accurate. However, since conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective, and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent. Convergent Concrete Technologies, LLC. sole warranty is that our products will meet our specifications at the time of shipment. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

CONVERGENT CONCRETE TECHNOLOGIES, LLC. SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. CONVERGENT DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Refer to www.convergentconcrete.com for latest Technical Data Sheet and MSDS.

Convergent Concrete Technologies, LLC. ~ Specialty Chemical Concrete Treatments • 115 North 1380 West • Orem, Utah 84057 • 801-375-2280

UNIQUE STRENGHTS, UNMATCHED PERFORMANCE™

©2013 Convergent Concrete Technologies, LLC. All Rights Reserved.

Pentra-Finish (HG) is a registered trademark of Convergent Concrete Technologies, LLC. Nano-Lithium brand name and logo are registered trademarks of Advanced Concrete Technologies, LLC ("ADVAN") and sub-licensed to Convergent Concrete Technologies, LLC, under a non exclusive co-brand/technology license. All rights reserved. Products manufactured and marketed by CONVERGENT CONCRETE TECHNOLOGIES, LLC are protected by U.S. Patent #8,299,151 and/or pending patents under license in the United States and other countries by ADVANCED CONCRETE TECHNOLOGIES, LLC makes no claim as to the product performance or product shown to be other than as warranted. REVISION DATE 022615