

# Stone | EDGE

## SURFACES

Professional Grade Concrete Overlays

# PRIMER

## applications



### DESCRIPTION (Primer 100)

Pre-mixed extreme bonding agent designed to permanently bond any Stone Edge Surfaces overlay Mixes to a painted or sealed concrete, masonry, plaster, drywall, glass, glazed tile, Styrofoam or adverse substrate. (See over Wood application video) 5 Gallon pail (approx. 700 sqft) or 1 Gallon Jugs (approx 150 sqft).

### DESCRIPTION (Primer 110)

Dry Mix (mix with water) Extreme bonding agent designed to permanently bond any of Stone Edge Surfaces overlay mixes to a painted or sealed concrete, masonry, plaster, drywall, glass, glazed tile, Styrofoam or adverse substrate. (See over Wood application video) 5 Gallon pail (approx. 1,400 sqft).

### MOST COMMON USES:

- Vertical Primer
- Horizontal Primer

### APPLICATION

**BASE/TOP COAT:** Primer Bond Coat

**THICKNESS:** Very Thin

**APPLICATION METHOD:** Roller, Brush, Spray

**WORKING TIME:** Re-Emulsifies one time

**PRODUCTS USED WITH:**

- Stamp, Trowel, Spray, Wall, MicroTop Mixes
- Spider Lath

**COMMONLY APPLIED OVER:**

- |  |  |
|--|--|
| • Spalled and Adverse Condition Concrete | • Wood (see over wood application video) |
| • Concrete                               | • Tile                                   |
| • Stucco                                 | • Painted Surface                        |
| • Cement Board                           | • Styrofoam                              |



For additional installation examples, images and training videos visit us online, call or email:

stoneedgesurfaces.com | 844-786-6333

info@stoneedgesurfaces.com

Stone EDGE Surfaces Division - Turey International Resources, LLC