

# Stone|EDGE SURFACES

Professional Grade Concrete Overlays



## DESCRIPTION

Spray Mix is a just add water polymer, “no-fiber”, very fine aggregate and additive enhanced concrete overlay mix that allows a 30 minute to 1-hour open time for spraying and troweling when applied over horizontal substrates. Spray mix is used in residential or commercial horizontal interior or exterior spray or trowel down concrete overlay applications to achieve spray texture (splattered) knockdown, thin coat, broom finish, and can be sprayed on vertical surfaces as well for troweling, and more. Comes in Gray or White 50 LB Bags.

## MOST COMMON USES

- Spray Texture Knock-down Finish Horizontally
- Spray Texture Knock-down Finish Vertically
- Spray Texture Finish Horizontally
- Spray Texture Finish Vertically
- Thin Coat Finish
- Thin Coat Broom Finish
- Base Coat for Stenciling
- Base Coat for Tape Down
- Pool Deck
- Driveway
- Patio

## APPLICATION

**BASE/TOP COAT:** Top Coat (also used as Base Coat)

**THICKNESS:** Thin, 1/32” to 1/8” Max

**APPLICATION METHOD:** Mortar Sprayer, Trowel

**WORKING TIME:** Average 30 Minutes to 1-Hour (depending on application process, temperature, and thickness)

**PRODUCTS USED WITH:**

- Primer 100 & Primer 110
- Liquid Colors & ColorPax
- Stains & Sealers

**COMMONLY APPLIED OVER:**

- Stable Substrate
- Concrete
- Wood (see over wood application video)
- Linoleum
- Tile
- Painted Surface
- Styrofoam
- Cement Board

# SPRAY MIX



For additional installation examples, images and training videos visit us online, call or email:

[stoneedgesurfaces.com](http://stoneedgesurfaces.com) | 844-786-6333

[info@stoneedgesurfaces.com](mailto:info@stoneedgesurfaces.com)

Stone EDGE Surfaces Division - Turey International Resources, LLC