

## Accent Enhancer

PRODUCT AND COMPANY IDENTIFICATION	
<b>PRODUCT MANUFACTURER:</b> Stone Edge Surfaces	<b>MANUFACTURER:</b> Turley International Resources, LLC.
<b>PRODUCT NAME:</b> Accent Enhancer	4322 South 80 <sup>th</sup> Street
	Mesa, AZ 85212 - USA
	TEL: 844-786-6333 E: info@stoneedgesurfaces.com
<b>EMERGENCY:</b> CHEMTREC P: 703-527-3887 F:703-527-3887 (International)	<b>MEDICAL:</b> 3E Company P:800-451-8346 F:760-602-8856 (International)
PRODUCT COMPOSITION	
Stone Edge Surfaces Accent Enhancer is a heterogeneous mixture of hydraulic cement, sand, and silica and proprietary additives. Accent Enhancer is part of a 2 Part mix and must be mixed with Primer 100 to create a "Post Mix" solution that is used to enhance the coloring process and add realism. Accent Enhancer is a dry cementitious mix that comes 17 lb. pail and is mixed with liquid Primer 100 or Primer 110.	
PRODUCT USES	
Stone Edge Surfaces Accent Enhancer is used to enhance the coloring process of vertical stamping applications such as Stack Stone, yet may also be used on horizontal overlay applications as well. Accent Enhancer is applied "prior" to the coloring process and is applied using a cellulose sponge to the high points of the stamped stone surface only...leaving just a film of product, which reacts to the colors applied afterwards to create the realistic worn, weathered look of natural stone. Also works in repairing shrinkage or hairline cracks in stamped concrete or overlays. By applying Flex- Accent Enhancer and then applying base colors, the Accent Enhancer allows the base colors to mottle the stamped stones in realistic and natural ways to give the stones a more natural appearance...just like real stone.	
PRODUCT CAUTIONS	
Use only a cellulose sponge to help reduce dripping and DO NOT use a sprayer! Accent Enhancer is to be applied sparingly with the intent to just highlight the higher portions (the tips and edges that stick out the furthest) and is not meant to fill every crack, crevice, or cover the surface completely.	
PRODUCT PHYSICAL PROPERTIES	
See SDS Sheet for Physical Properties and Safety Information	
PRODUCT BENEFITS	
May be either sprayed or rolled onto surface like paint	Contributes to USGBC credits under LEED rating system
Warranted bond ability	Abrasion and wear resistant
Moisture tolerant and breathable	Gives more natural stone appearance
Very low influence from concrete vapor emission	Easy to apply with cellulose sponge
PRODUCT CLEANABILITY	
Overlay products, the smoother the finished texture, the easier the surface is to clean, but there is a loss of skid resistant properties. Cleaning and disinfecting compounds and cleaning techniques can affect the color, gloss, texture and performance of the system. As the precautionary step, Stone Edge Surfaces recommends that the end-user test their cleaning and disinfecting compounds on a non-conspicuous area before use.	
PRODUCT COVERAGE	
Approximate Surface Area Coverage for Accent Enhancer: 1000 sqft per pail of Accent Enhancer mixed with Stone Edge Surfaces Primer 100 or Primer 110.	
PRODUCT SHELF LIFE	
If properly stored, the expected shelf life can exceed 6 months. However, it is recommended that product be used as soon as possible after delivery. Rotate stock to use oldest inventory first. Store under roof and keep dry.	
PRODUCT LIMITED WARRANTY	
<p>Limited Warranty: Stone Edge Surfaces, a division of Turley International Resources, LLC., (further known as manufacturer), products are warranted to be free of manufacturers defect in material and formulation for 90 days (the warranty period) from the date of purchase from manufacturer, when applied per manufacturer's instructions, and as provided specifically in the terms and conditions herein. TERMS: Upon verification of factory defect, manufacturer reserve the right, at its sole discretion, to replace the product purchased or refund the purchase price paid to the manufacturer. The refund amount will be based on the most current product pricing at the time warranty coverage is approved. For Products to be deemed warrantable, they must be inspected and warranty approved by an authorized manufacturer representative. This Limited Warranty does not cover, nor is manufacturer responsible for, any project costs or delays, and no remedies will be made for loss and/or usage of fuel, labor, demolition, haul away, clean up, service, travel, transport, reapplication, parts, or any other costs in excess of the purchase price of the products paid to the manufacturer or use of resources resulting from a failure of a warrantable product. Warranty also does not cover products that have been modified, altered, improper mixing not in accordance with manufacturers guidelines or instructions, misused or used in a way not recommended by manufacturer, used after shelf life expiration, acts of God, adverse environmental conditions beyond manufacturers control, inadequate contractor skill level or quality of contractor workmanship, fading over time, improper prep of application area, chemical damage, unstable, cracking or shifting substrate causing product failure. Product replacement or refund of product purchase price from manufacturer are manufacturer's sole obligations under this limited warranty.</p>	