

Stone | EDGE

SURFACES

Professional Grade Concrete Overlays



DESCRIPTION

Trowel Mix is a just add water polymer, fiber, fine aggregate and additive enhanced concrete overlay mix that allows a 2 to 6 hour open time for troweling, broom finishing, hand texturing when applied over horizontal substrates. Trowel mix is used in residential or commercial horizontal interior or exterior trowel down concrete overlay applications to achieve textured, troweled, broom, skip trowel, free hand, broom finish and more. Comes in Gray or White 50 LB Bags.

MOST COMMON USES

- Hand Troweled Finish Horizontal Concrete Overlay
- Broom Finished Horizontal Concrete Overlay
- Aggressive Spray Texturing (Vertically & Horizontally)
- Vertically Troweled Pargings over Concrete, Block or Brick
- Textured, Skip Troweled Finish
- Tape Downs
- Stencil Top Coat
- Floors
- Concrete Decks
- Wood Decks (see over wood application video)
- Driveway
- Patio
- Pool Deck
- Sidewalk / Walkway

APPLICATION

BASE/TOP COAT: Top Coat (also used as Base Coat)

THICKNESS: Thin, 1/8" to 3/8" Max

APPLICATION METHOD: Trowel, Stencil, Free Hand

WORKING TIME: Average 2 to 8 hours (depending on application process, temperature, and thickness)

PRODUCTS USED WITH:

- Primer 100 & Primer 110
- Liquid Colors & ColorPax
- Stains & Sealers

COMMONLY APPLIED OVER:

- Stable Substrate
- Concrete
- Wood (see over wood application video)
- Cement Board
- Linoleum
- Tile
- Painted Surface
- Styrofoam

TROWEL MIX



For additional installation examples, images and training videos visit us online, call or email:

stoneedgesurfaces.com | 844-786-6333

info@stoneedgesurfaces.com

Stone EDGE Surfaces Division - Turey International Resources, LLC