Stone EDGE SURFACES **Professional Grade Concrete Overlays**

Stone EDGE WALL MIX (GRAY)

DESCRIPTION

Wall Mix is a just add water polymer, fiber, aggregate and additive enhanced concrete overlay mix that allows a 1 to 6-hour open time for stamping or carving when applied over vertical or inverted substrates. Wall mix is used in residential or commercial vertical interior or exterior stamp or hand carve concrete overlay applications to achieve the realistic look of brick, wood, natural stone, manufactured stone, stackstone, rocks and more. It can also be used underwater to create in commercial aquariums to create natural looking aquatic habitats, stonescapes, cliff faces and more. Comes in Gray or White 50 LB Bags.

MOST COMMON USES

- Deep Stamped (Stackstone) Fireplaces & Fire Pits
- Texture Stamped Wall
- Hand Carved wall
- Boulders, Rocks, Grotto, Cliff Face, Caves
- Seat Walls (Hardscapes)
- Water Features & Fire **Boulders**
- Outdoor Kitchens & BBQ's

- · Matching existing brick, stone, wood, etc.
- Artistic sculpture
- Over Styrofoam to create the look of wood beams. trees, rocks, and more
- · Smooth modern look of concrete
- · As a scratch coat

APPLICATION

BASE/TOP COAT: Top Coat (also used as Base Coat) **THICKNESS:** 1/4" to 3"+ (Average is 3/4" for stamp/carve) APPLICATION METHOD: Trowel, Hawk & Trowel, Throw WORKING TIME: Average 1-6 Hours (depending on application process, temperature, and thickness)

PRODUCTS USED WITH:

- Primer 100 & Primer 110
- Liquid Colors & ColorPax
- Stains & Sealers

COMMONLY APPLIED OVER:

- Stable Substrate Drvwall
- Stvrofoam
 - Lath
 - Plaster
- Block Brick
- Painted Surface
- Cement Board
- Stucco Concrete Wood

WALL MIX



For additional installation examples, images and training videos visit us online, call or email:

stoneedgesurfaces.com | 844-786-6333

info@stoneedgesurfaces.com

Stone EDGE Surfaces Division - Turey International Resources, LLC