

ENDURABLE CONCRETE SEALER™



- Available in matte and gloss
- Easy to apply via sprayer, t-bar microfiber applicator, or roller
- Low VOC content
- Low odor
- Heavy duty
- Perfect for forklift traffic, parking garages, and other commercial applications
- Excellent UV stability - will not yellow or degrade in sunlight
- Anti-graffiti - excellent resistance to solvents
- Safe for countertop use
- Excellent chemical resistance
- Excellent durability and scratch resistance
- Excellent resistance to hot tire pickup
- Excellent versatility allows for interior and exterior use. Use on residential or commercial applications
- Excellent coverage makes product very cost-effective

ENDURABLE CONCRETE SEALER is a revolutionary sealer created from cutting edge polyurethane technology that allows for maximum penetration, durability, and chemical resistance, while still delivering ease of application.
COVERAGES RATES: 300 – 800 square feet per gallon depending on porosity of surface.
PACKAGING: Concentrate that makes 1.12 gallons, 4.5 gallons, & 9 gallons (9 gallon concentrate may be made 4.5 gallons at a time.)
MIX RATIO: Water is mixed with the sealer components at a ratio of 2 parts water to 1 part mixed sealer components (for fastest dry times on smooth surface concrete, mix the second coat of sealer at 1 part water to 1 part mixed components.)
SHELF LIFE AND STORAGE: Product has a shelf life of a minimum of 1 year in original containers. Store product between 40 and 77 degrees Fahrenheit. Keep product free from excessive heat, moisture, and freezing.

WHERE TO USE: Concrete – garages, driveways, patios, walkways, countertops, pool decks, commercial floors, etc., masonry, terrazzo, and natural stones.
MAINTENANCE: Use mild detergent solutions, light vinegar solutions, or light ammonia solutions. Reseal as necessary – 5 to 10 years depending on traffic and usage. Routine buffing with a light pad on a low-speed buffer can help maintain an even sheen and a clean surface.

DURABILITY AND CHEMICAL TESTING AND PERFORMANCE RESULTS:

Abrasion Resistance	H-18 1000 cycles, mg loss	ASTM D 4060	260
Abrasion Resistance	CS-17 1000 cycles, mg loss	ASTM D 4060	25
Modulus of Elasticity, kpsi	ASTM D 638	175-300	
Tensile Strength, psi	ASTM D 638	4400-7200	
Tear Strength, pli	ASTM D 624	150-300	
Artificial Weathering	ASTM D 4587	None	
VOC Content	ASTM D3960	< 1%	
Pendulum Hardness Test	ASTM D4366 1 Day - Matte- 38 seconds/Gloss-38 seconds		
Pendulum Hardness Test	ASTM D4366 5 Day -Matte- 154 seconds/Gloss-174 seconds		
Pendulum Hardness Test	ASTM D4366 7 Day -Matte-162 seconds/Gloss-184 seconds		
Coefficient of Friction Test	ASTM D-2047 Dry – 0.6	Wet – 0.47	
Water Vapor Transmission	ASTM E 96	1.26 grains/hour/square foot	

APPLICATION INSTRUCTIONS: FOR POLISHED CONCRETE, YOU MUST FOLLOW THE ARCHITECTURAL SPECS AVAILABLE ON THE DROP-DOWN MENU AT ENDURABLEPRODUCTS.COM. FOR ALL OTHER APPLICATIONS, FOLLOW THE INSTRUCTIONS BELOW.

For optimum results, open troweled concrete mechanically. Apply to dry, porous concrete. Mix Component 1 with Component 2, then mix with twice as much water as components. Use a mixing drill and paddle for minimum of 2 minutes. Pot life is 45 to 90 minutes on matte and 90 to 180 minutes on gloss. Do not apply 2nd coat until 1st coat is completely dry. Product may be applied via pump sprayer with a conical tip .05 to .15 gpm at 40 psi, airless sprayer, or T-Bar micro-fiber applicator. When applying over stain, it is recommended to spray the first coat to avoid movement of color residue. Second coat MUST be applied via microfiber T-Bar applicator or low-speed buffer when dealing with smooth surface floors. Second coat may be applied via sprayer on most exterior concrete. **PRODUCT SHOULD BE MIXED 1 TO 1 WITH WATER ON SECOND OR SUBSEQUENT COATS WHEN APPLYING OVER NON-POROUS OR SMOOTH SURFACES. DO NOT OVER-APPLY.** Coverage rates are typically between 300 and 500 square feet per gallon per coat on the first coat depending on porosity of surface. Subsequent coats or low porosity surfaces may yield higher coverage rates of 500-800 square feet per gallon. Before application of sealer, make sure surface is free from dirt, oils, previous sealers, etc. It must be applied in thin coats. Two coats are usually sufficient, but applicator must determine the specific need. Sealer should be applied between 40 and 90 degrees Fahrenheit. After applying the first coat, wait until the sealer is dry to the touch, usually 45 to 180 minutes for matte, 3-6 hours for gloss, depending on temperature and air flow, and then subsequent coats may be applied. Subsequent coats typically take 3 to 8 hours to dry for matte and 6 to 24 hours for gloss depending on temperature and air flow. After application, tools may be cleaned using soap and water. Light traffic is possible after 8-24 hours and heavy traffic is possible after 24-48 hours. The sealer will gain strength over the next few days after application and will reach full cure at 7-10 days. Avoid subjecting the sealer to freezing temperatures or moisture for 12-36 hours after application. Make sure substrate is dry before application. ENDURABLE CONCRETE STAIN can penetrate product for the first 4 hours after sealer is dry when stain is mixed in water. ENDURABLE CONCRETE STAIN may penetrate product when mixed in acetone for the first two days after application. If applying stain mixed in acetone over sealer, spray VERY lightly. Too much acetone can “cook” the sealer. Upon further curing, the stain cannot penetrate unless an additional coat of product is applied. Only ENDURABLE VERTICAL STRIPPER may remove products when sealer is fully cured. This requires the stripper to be covered and remain wet for a minimum of 12 to 24 hours. **FOR TIPS AND TECHNIQUES, VISIT OUR WEBSITE AT WWW.ENDURABLEPRODUCTS.COM UNDER THE ENDURABLE CONCRETE SEALER DROP-DOWN MENU.** It may be beneficial to strain product before use.


CHEMICAL RESISTANCE TESTING ACCORDING TO ASTM D 1308
 Product cured for 14 days at 70 degrees Fahrenheit before testing

CHEMICAL	Time- 4 hours	Time-24 hours
Betadine	No Effect	No Effect
Bleach	No Effect	No Effect
Gasoline	No Effect	No Effect
Acetic Acid	No Effect	No Effect
Water	No Effect	No Effect
MEK (complete immersion)	Slightly Soft	Soft
Brake Fluid	No Effect	Slightly Soft
H2SO4	No Effect	No Effect
IPA	No Effect	Slightly Soft
HCl	No Effect	No Effect
Skydrol	No Effect	No Effect
NaOH	No Effect	No Effect
NH4OH	No Effect	No Effect

LIMITATIONS: Product should be applied in thin coats. Do not over-apply. Product must be applied to clean, dry substrates. It is recommended to apply to porous surfaces for longest-lasting results. Product should not be applied to concrete with moisture related issues. If moisture issue is suspected, email info@endurableproducts.com to get a recommendation on how to deal with the moisture issues prior to application of sealer.
WARNINGS: Use with proper ventilation. May cause eye and skin irritation. If you experience headaches, dizziness, or watery eyes, you may wear a NIOSH TC-84 respirator during application.
WARRANTY: Evaluate whether this product is suitable for your intended application. control and vary widely, the following is made in lieu of all express or implied warranties of merchantability. Our only obligation and your only remedy is replacement of product, at the option of HDIP INC. In no case will HDIP INC be liable for any direct, indirect, special, incidental, or consequential damages including lost profits, goodwill, or business opportunity.

PRODUCT AVAILABILITY: Product is available at retail distributors around the world. Visit www.endurableproducts.com to find the nearest distributor.
SLIP RESISTANCE AND CLEANABILITY: The profile of the concrete will dramatically affect the slip-resistance. Aggressive finishes, such as broom-finished concrete, will yield the best coefficient of friction and will be slightly more challenging to clean. Smooth surfaces will yield a lower coefficient of friction but are easier to clean. If desired, additional slip resistance can be added to the sealer. 100 mesh polypropylene will work well and should be applied in the second coat. It is best to mix it into the sealer and then apply with a T-Bar or the additive can be broadcast into the sealer. When slip-resistant additive is used, it is recommended to mix the sealer 1 to 1 with water to help keep the additive in solution. It is also recommended to apply a third coat of sealer to completely encompass and protect the additive.

"It's sealer that really works!"
 MARK CHEW - SPECIALTY DIVISION MANAGER
 LOGAN CONTRACTORS SUPPLY
"It's the best sealer I've ever seen and I have over 30 years of experience in the industry."
 STEVE CREASY - JUST CONCRETE FLOORS



All products are labeled with full instructions. Additional information may be found on technical data sheets available at our website: www.endurableproducts.com. You may also view helpful instructional videos available on the website.

ENDURABLE CONCRETE PRODUCTS™

The website provides additional tips and techniques for the individual products. Color selections are also available on website.

www.endurableproducts.com

800-910-3120