

# Solid Color Water Based Acrylic Sealer

[Durável LBA](#) is a specially formulated, ready-to-use Liquid Bonding Agent that is designed to bond cementitious materials to porous concrete surfaces. Durável LBA is a thin primer for several Durável systems and is available in 1-gallon jugs and 5-gallon pails.

## Typical Uses:

- **Bonding Agent For Durável TRM**
- **Bonding Agent For Durável SOM**
- **Very Porous Surfaces Prior To Trowel Overlay**
- **Optional Primer For In-Fluence Stains**

## Product Advantages :

- **Improves Bond Of Overlays To Concrete**
- **Simple Ready-To-Use Formula**
- **Slows Hydration, Increases Working Time**
- **Low Odor**

Ready to use

Application Temperature, Substrate  
45° to 90° F

VOC Content  
< 10 g/L

Packaging:  
1-Gallon Jugs | 5-Gallon Pails

## Coverage:

150 to 200 sq ft per gallon depending on the porosity of the profiled surface. Apply in a test area to determine actual coverage.

## Directions for Use:

### Substrate Preparation:

Follow the substrate preparation instructions for the selected repair mortar, overlay product, or top coat.

### Mixing Instructions:

Material should be stirred well prior to application. Long term storage may allow material to separate.

When used as a primer for In-Fluence stains dilute 48 oz of Durável LBA with 80 oz of water.

### Application Instructions:

Apply by pump up sprayer, paint roller, or brush in a thin, uniform coat. DO NOT allow product to pond or puddle during application. Avoid material accumulating in joints and low spots by brushing out ponding or backrolling the surface. Overapplication or creating a heavy surface film can cause a bond failure for subsequent coatings.

Wait for LBA to get tacky or dry before installing overlay concrete materials. Overlay coatings may be installed after approximately 30 minutes but no more than 24 hours after application (@ 70 F and 50 % humidity). After 24 hours LBA

**FOR PROFESSIONAL USE ONLY**

**SURFACE PREPARATION**

**Technical Data**

# Technical Data Sheet

must be applied again as if it were the first time. Do not apply Durável LBA if the substrate is damp or frozen. Do not apply when the air or substrate temperature is below 45°F (7°C) or above 90°F (32.2°C).

## Clean Up:

Clean tools, sprayers, and mixing vessels with soap and water.

## Storage:

Store in a well-ventilated place. Keep container tightly closed. Protect product from freezing.

## Disposal:

Recycle and/or dispose of contents and containers in accordance with local, regional, national, and international regulations.

## Shelf Life:

Up to one year from original manufacture date when stored in its original, unopened container at room temperature. May be extended with reasonable care.

## Limitations:

This product is not intended for public use and is intended for use by qualified contractors and installers with proper experience and training in the use of these products, and that have read the complete safety data sheet. Apply product only when substrate and ambient temperatures are within the accepted range.

## Warranty:

IMPORTANT!

Before using any Durável product, read and understand its accompanying Safety Data Sheet & Application Instructions for important safety information.

STANDARD TERMS AND CONDITIONS OF SALE, INCLUDING STANDARD WARRANTY APPLY – VISIT [Duravel.com](http://Duravel.com) FOR THE LATEST VERSION.

## Disclaimer:

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Durável assumes no responsibility for injury to vendee or third party person proximately caused by

# Technical Data Sheet

the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, Durável assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety precautions are followed.

## Safety Instructions:

### For Professional Use Only

### Keep Out of Reach of Children and Animals

IF IN EYES: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs. IF ON SKIN: (or hair) Wash contaminated skin with plenty of soap and water. Remove contaminated clothing and shoes. Get medical attention if irritation occurs. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if breathing becomes difficult. IF SWALLOWED: Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Get medical attention if symptoms occur.

Do not use a solid water stream as it may scatter and spread fire. The product itself does not burn

**Always Review SDS & Technical Data Prior to Use**